

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Isotropic Flexible Rubber Magnetic

**Product Code::** CGMAG06 / CGMAG09

**Supplier Information** 

Company Name: CGATE GROUP info@cgategroup.com

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance/Preparation:** Preparation

Ingredients Name	Content/%	CAS NO.
Polyvinylchloride	3-5%	9002-86-2
SrO6Fe2O3	28-30%	-
Polyethylene	60-65%	8013-07-8
EBSO	0.5-1%	-
DOP	0.5-1%	-

Note: See Section 8 of MSDS for exposure limit data for these ingredients.

#### The preparation is not classified as dangerous under the Hazard Communication Standard

This MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of the product.

## 3. HAZARDS IDENTIFICATION

#### **Emergency Overview**

Under standard conditions of use, this product is not expected to create any unusual emergency hazards. This is a non-combustible, non-reactive solid material. Use methods suitable to fight surrounding fire. Contact with the eye may result in mechanical irritation characterized by itching or redness.

Due to product form, exposures to dusts and fumes are not expected to occur. If this product is cut with power cutting equipment (such as saws), dust generated may cause respiratory irritation, and congestion in extreme cases. Prolonged and excessive skin contact may result in slight irritation.

Routes of Exposure: Inhalation, skin, and eye contact.

Version update: 2019-07-17 Page 1 of 7



#### **Potential Health Effects**

Eyes: Particulates from this product may cause mechanical irritation of the eye from cutting, grinding or drilling of the

product. Continued mechanical irritation of the eye could result in permanent corneal damage.

Skin: This product may produce skin abrasions. Mechanical rubbing may increase skin irritation.

**Ingestion:** Not a likely route of entry.

**Inhalation:** Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the

respiratory tract.

HMIS Ratings: Health: 0 Fire: 1 Physical Hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

## 4. FIRST AID MEASURES

**Eye contact:** Do not rub or scratch eyes. Dust particles may cause eyes to be scratched. Flush eyes with large amounts of water for 5-15 minutes. If irritation persists, contact a physician.

Skin contact: Wash exposed skin with soap and water. If irritation develops or persists, seek medical attention.

**Ingestion:** Product is not intended to be ingested or eaten. If the product is ingested, do not induce vomiting. Seek medical

attention.

**Inhalation:** Move person to non-contaminated air. Call a physician if symptoms develop or persist.

## 5. FIRE FIGHTING MEASURES

Flammable Properties
Flash Point: None
Flammable limits
LFL: Not Applicable
UFL: Not Applicable

**General Fire Hazards:** See Section 9 for Flammability Properties. None expected.

**Hazardous Combustion Products** 

Version update: 2019-07-17 Page 2 of 7



The decomposition products from this material are those that would be expected from any organic (carbon-containing) material, and are mainly derived from pyrolysis, or burning, of the polymer. These decomposition products may include carbon dioxide, carbon monoxide, carbon particles, hydrocarbons, chlorine, hydrogen, chloride, phosgene, and formaldehyde. This product should not be burned as construction waste.

**Extinguishing Media:** Use any media suitable for the surrounding fires. Water, spray, fog, carbon dioxide (CO2), dry chemical, foam.

#### Fire Fighting Equipment/Instructions

Firefighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Firefighters should avoid inhaling any combustion products. Do not release chemically contaminated water into drains, soil or surface water.

NFPA Ratings: Health: 0 Fire: 1 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

## 6. ACCIDENTAL RELEASE MEASURES

## **Containment Procedures**

None necessary.

## **Clean-Up Procedures**

Sweep up or gather material and place in appropriate container for disposal. This product should not be burned as construction waste.

#### **Evacuation & Special Procedures**

None necessary.

## 7. HANDLING AND STORAGE

#### **Handling Procedures**

Customary personal hygiene measures, such as washing hands after working with these products are recommended.

#### **Storage Procedures**

Room temperature - normal conditions. Warehouse storage should be in accordance with package directions, if any. Material should be kept dry, and protected from the elements.

Version update: 2019-07-17 Page 3 of 7



## 8. EXPOSURE CONTROLS, PERSONAL PROTECTION

Exposure limit values: not applicable.

#### **Engineering Controls**

No special protective measures are necessary for use of this product in that it is an article, and under normal conditions of use is not expected to release, or otherwise result in exposure to a hazardous chemical.

#### PERSONAL PROTECTIVE EQUIPMENT

### Personal Protective Equipment: Eyes/Face

Safety glasses with side-shields may be worn to reduce the risk of eye injury due to construction related activities.

## Personal Protective Equipment: Skin

Under normal conditions of use this product is not expected to cause skin irritation. To reduce the risk of skin irritation due to construction-related activities leather or other appropriate work gloves are recommended.

#### **Personal Protective Equipment: Respiratory**

No special ventilation systems are required under normal conditions of use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Working temperature:** Operation temperature range is recommended from -15°F to 160°F (-26°C to 71°C).

Flexibility: At 68°F (20°C), our high-quality magnetic material can be coiled to a 1/2" (12.7mm) radius without cracking.

Hardness: Shore D35.

**Machinability:** Die cuts and knife cuts cleanly and easily.

Density: 3.6 g/cm<sup>3</sup>.

Multi-Pole Spacing: 12.7 poles per inch.

**Solubility in Water:** Insoluble

Viscosity: Not Applicable

Appearance: sheets OR rolls

Color: Various (mainly white ).

Version update: 2019-07-17 Page 4 of 7

MSDS Number: CT 10085-1



# Material Safety Data Sheet Isotropic Flexible Rubber Magnetic

Odor: Negligible

Freezing Point: Not Applicable

Evaporation Rate (n-Butyl Acetate=1): Not Applicable

## 10. STABILITY AND REACTIVITY

## **Chemical Stability**

Stable under normal conditions.

#### **Chemical Stability: Conditions to Avoid**

None identified.

## Incompatibility

None identified.

## **Hazardous Decomposition**

The decomposition products from this material are those that would be expected from any organic (carbon-containing) material, and are mainly derived from pyrolysis, or burning, of the polymer. These decomposition products may include carbon dioxide, carbon monoxide, carbon particles, hydrocarbons, chlorine, hydrogen, chloride, phosgene, and formaldehyde.

## **Possibility of Hazardous Reactions**

None expected.

## 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity data

No toxicity data available for this product.

## Carcinogenicity:

# PVC (Chloroethylene, polymer) (9002-86-2)

IARC: Supplement 7, 1987; Monograph 19, 1979 (Group 3 (not classifiable))

#### Mutagenicity

No information available for the product.

## Teratogenicity

No information available for the product.

MSDS Number: CT 10085-1



# Material Safety Data Sheet Isotropic Flexible Rubber Magnetic

### **Developmental Effects**

No information available for the product

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

#### **General Product Information**

No information available for the product.

## **Component Analysis - Ecotoxicity - Aquatic Toxicity**

No ecotoxicity data are available for this product's components.

#### **Environmental Fate**

No information available for the product.

#### 13. DISPOSAL CONSIDERATIONS

Subject to legislation by local authorities, the product can be disposed of together with domestic refuse and industrial waste. Waste and residues can be incinerated in a plant equipped with flue gas washing, together with domestic waste.

## 14. TRANSPORT INFORMATION

**Proper shipping name:** This product is not classified a hazardous material for transport.

Hazard class: None
Packing group: None
Identification number: None

**DOT:** This product is not classified a hazardous material for transport.

## 15. REGULATORY INFORMATION

Product is not considered to be a hazardous chemical under the Hazard Communication Standard.

#### **Inventory Status**

Inventory Status

United States (TSCA) All ingredients are on the inventory or exempt from listing.

Version update: 2019-07-17 Page 6 of 7



This plastic foam does not require marking under the dangerous substances and preparation directives 67/548/EWG and 1999/45/EG.

## 16. OTHER INFORMATION

**Issue Date:** Dec. 27, 2007

This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, are made with respect to the product or the information and recommendations. We make no representation as to completeness or accuracy. In no event we shall be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.

\* \* \* END OF MSDS \* \* \*

Version update: 2019-07-17 Page 7 of 7